

The Delphion Integrated View

Get Now: PDF | More choices... Tools: Add to Work File: Create new Wo View: INPADOC | Jump to: Top Go to: Derwent... **⊠** Ema

> **Title:** JP7029560A2: SEPARATOR FOR SEALED LEAD-ACID BATTERY

JP Japan **P**Country:

> **VKind:** Α

VInventor: **MUTOU JIYUNSUKE:**

HOSONO HIROAKI:

NIPPON SHEET GLASS CO LTD **P**Assignee:

News, Profiles, Stocks and More about this company

1995-01-31 / 1993-07-12 Published / Filed:

PApplication

JP1993000171521

Number:

VIPC Code: H01M 2/16;

Priority Number: 1993-07-12 JP1993000171521

PAbstract:

PURPOSE: To provide a separator for a sealed lead-acid battery by which high pressure force can be maintained in the battery.

CONSTITUTION: In a separator mainly composed of glass fiber. the separator for a sealed lead-acid battery is formed by mixing the glass fiber, silica powder and silica sol extractively. Thereby, only under the coexistence of the silica power and the silica sol, an excellent gel condition is formed in the separator in a drying process after they are mixed extractively, and pressure force is maintained by the expansive action. After electrolyte is injected, the pressure force can be maintained sufficiently without reducing the pressure force applied to a plate. The service life of the battery can be lengthened significantly.

COPYRIGHT: (C)1995,JPO

None **P**Family:

CHEMABS 122(18)218616Q CAN122(18)218616Q DERABS C95-**POther Abstract**

103012 DERC95-103012 Info:









this for the Gallery...

© 1997-2003 Thomson Delphion

Research Subscriptions | Privacy Policy | Terms & Conditions | Site Map | Contact U: